



Availability

ShoreView

ShoreView Mini

CR-39	●	●
Polycarbonate	●	●
Trivex	●	●
1.60 Index	●	●
Transitions Gray	●	●
Poly Transitions Gray	●	
1.60 Transitions Gray		●
1.56 SunSensors Gray	●	●
Poly Photochromic Gray	●	●
1.56 Photochromic Gray	●	●
Polarized Gray	●	
Poly Polarized Gray	●	

ShoreView & ShoreView Mini are the latest generation progressive designs that offer a premier value alternative for your business.

ShoreView & ShoreView Mini offer wide distance vision, comfortable wear, smooth, seamless transition from far to near, and easy adaptation.

Shore View fits at 18mm, and ShoreView Mini fits at 15mm.

Price competitive, modern design, and customer satisfaction; ShoreView & ShoreView Mini fit all your needs.

ShoreView

Diameter	Material	Base Curves	Rx Range	Add Powers	Min Fit
75/80	CR-39 Uncoated	2.25, 4.25, 5.50, 7.50	-9.00 to +6.00, Cyl -4.00	+0.75 to +3.50 in .25 steps	18mm
75/80	CR-39	2.25, 4.25, 5.50, 7.50	-9.00 to +6.00, Cyl -4.00	+0.75 to +3.50 in .25 steps	18mm
75/80	Poly	2.00, 4.00, 5.50, 7.25	-9.00 to +6.00, Cyl -4.00	+0.75 to +3.50 in .25 steps	18mm
75/80	1.60 Index	1.50, 3.00, 4.00 5.00, 7.00	-9.00 to +6.00, Cyl -4.00	+1.00 to +3.50 in .25 steps	18mm
75/80	Trivex	3.00, 4.00, 5.00, 7.00	-9.00 to +6.00, Cyl -4.00	+1.00 to +3.50 in .25 steps	18mm
75/80	Transitions Gray	3.00, 4.00, 5.00, 7.00	-8.00 to +7.00, Cyl -4.00	+1.00 to +3.50 in .25 steps	18mm
75/80	1.56 Photochromic Gray	1.50, 3.00, 5.25, 7.00	-9.00 to +6.00, Cyl -4.00	+0.75 to +3.50 in .25 steps	18mm
75/80	ShoreExec Poly Trans Gray	2.00, 4.00, 5.50, 7.25	-9.00 to +6.00, Cyl -4.00	+0.75 to +3.50 in .25 steps	18mm
75/80	Poly Photochromic Gray	2.50, 4.00, 5.25	-9.00 to +6.00, Cyl -4.00	+1.00 to +3.00 in .25 steps	18mm
75/80	1.56 SunSensors Gray	2.25, 4.25, 5.50, 7.50	-9.00 to +6.00, Cyl -4.00	+1.00 to +3.50 in .25 steps	18mm
75/80	CR-39 Polarized Gray	2.00, 4.00, 5.50, 7.50	-9.00 to +6.00, Cyl -4.00	+0.75 to +3.50 in .25 steps	18mm
75/80	Poly Polarized Gray	2.00, 4.00, 5.50, 7.50	-9.00 to +6.00, Cyl -4.00	+0.75 to +3.50 in .25 steps	18mm

ShoreView Mini

Diameter	Material	Base Curves	Rx Range	Add Powers	Min Fit
70/75	CR-39 Uncoated	1.00, 3.00, 5.00, 7.00	-9.00 to +6.00, Cyl -3.00	+1.00 to +3.00 in .25 steps	15mm
70/75	CR-39	1.00, 3.00, 5.00, 7.00	-9.00 to +6.00, Cyl -3.00	+1.00 to +3.00 in .25 steps	15mm
75/80	Poly	2.75, 4.75, 6.75, 7.75	-9.00 to +8.00, Cyl -4.00	+1.00 to +3.00 in .25 steps	15mm
75/80	1.60 Index	1.50, 3.00, 4.00 5.00, 7.00	-9.00 to +6.00, Cyl -4.00	+1.00 to +3.50 in .25 steps	15mm
75/80	Trivex	3.00, 4.00, 5.00, 7.00	-9.00 to +6.00, Cyl -4.00	+1.00 to +3.50 in .25 steps	15mm
75/80	Transitions Gray	3.00, 4.00, 5.00	-8.00 to +7.00, Cyl -4.00	+1.00 to +3.50 in .25 steps	15mm
75/80	1.56 Photochromic Gray	1.50, 3.00, 5.25, 7.00	-9.00 to +6.00, Cyl -4.00	+0.75 to +3.50 in .25 steps	15mm
75/80	Poly Photochromic Gray	2.00, 3.50, 5.00, 6.00	-9.00 to +6.00, Cyl -4.00	+1.00 to +3.00 in .25 steps	15mm
75/80	1.60 Transitions Gray	1.50, 3.00, 4.00 5.00, 7.00	-10.00 to +7.00, Cyl -4.00	+1.00 to +3.50 in .25 steps	15mm
70/75	1.56 SunSensors Gray	1.00, 3.00, 5.00, 7.00	-9.00 to +6.00, Cyl -3.00	+1.00 to +3.00 in .25 steps	15mm

